

# **Z 205**HIGH ACID EMULSION BOWL CLEANER

# **Toilets**

# **Porcelain**



# **Urinals**

## Product Description

A high acid cleaner formulated to remove scale, rust and hard water deposits, from toilet bowls and urinals. Contains 23% inhibited hydrochloric acid and specially selected detergents to quickly and completely attack the most stubborn deposits. The special inhibitors protect plumbing, once soils are flushed away.

#### est: Limit:

Acid Content: $23.5 \pm 0.5\%$ Color:WhiteOdor:AcidicpH(concentrate):0.5 - 1.0

Base: Hydrochloric acid

Viscosity: Water thin Foam: Moderate Abrasives: None Inhibited: Yes Rust Removal: Excellent Excellent Detergency: Rinsability: Excellent Fumes: None

Flash Point: None (waterbased)

Biodegradability: Complete Storage/Stability: 2 years

Weight Per Gallon: 9.80 lbs. per gallonFreeze / Thaw Stability: Keep from freezing

#### **Directions For Use**

# FOR INSIDE OF TOILET BOWLS AND URINALS ONLY.

DO NOT USE ON MARBLE, TER-RAZZO, STAINLESS STEEL, CHROME, ALUMINUM OR PLAS-TICS. SPOT TEST ON UNKNOWN SURFACES.

FOR CLEANING TOILET BOWLS & URINALS: Flush toilet and use swab mop to push water from the bowl over trap. Press swab mop against bowl to remove excess water, then saturate mop with bowl cleaner while holding bottle and applicator over bowl. Swab bowl or urinal completely making sure to get under the rim. Let stand for 10 minutes then flush. Rinse applicator completely.

WEAR RUBBER GLOVES AND GOGGLES OR FACE SHIELD AT ALL TIMES.

2/00

#### MATERIAL SAFETY DATA SHEET

Prepared by: Regulatory Affairs Dept.

(Prepared According to 29 CFR 1910.1200)

Effective Date: 5/99 Revision: n/a

#### SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Z 205

Generic Name: High Acid Emulsion Bowl Cleaner Chemical Family: Hydrochloric Acid/Detergent Blend

Formula: Proprietary

Supplier's Name: Zagers Brand, Inc.

Supplier's Address: 4320 Gandy Blvd., Tampa, FL 33611

**Supplier's Phone #:** (800) 241-4797

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Hydrochloric Acid	7647-01-0	23 min	C5 ppm	C5 ppm	N/A
Nonionic Surfactant	9016-45-9	0 to 5			
Acrylic Latex	N/A	0 to 5			

SECTION 3-PHYSICAL DATA		SECTION 4 FIDE AND EX	SECTION 4-FIRE AND EXPLOSION HAZARD DATA			
SECTION 5-FHISICAL DATA		SECTION 4-FIRE AND EA	SECTION 4-FIRE AND EAT LOSION HAZARD DATA			
Boiling Point (°F): 205 F.	Specific Gravity: 1.175	Flash Point (Method Used): N/A				
Vapor Pressure: 33mm Hg @ 68 F.	Vapor Density (Air=1): >1	Upper Explosion Limit: N/A	Lower Explosion Limit: N/A			
% Volatile: 90+	<b>pH:</b> 0.5-1.0	Extinguishing Media: N/A				
Solubility in Water: Complete	Evaporation Rate (Water=1): <1	Special Firefighting Procedures: Non	Special Firefighting Procedures: Non Flammable			
Physical Description: Thin white opaque liquid with pleasant odor.		Unusual Fire and Explosion Hazards:	Unusual Fire and Explosion Hazards: N/A			

#### **SECTION 5-REACTIVITY DATA**

Stability: Stable

Hazards Decomposition Products: Hydrogen gas formed on contact with metals. HCL vapors emitted when heated. Chlorine gas may form by electrolysis or oxidation.

Hazardous Polymerization: None

Incompatibility (Materials to Avoid): Corrosive to many materials. Strong alkalis or oxidizers, bleaching agents, amines and carbonates. Contact with metals, metal oxides, soft metals and iron may generate hydrogen gas.

#### SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Do not mix with alkali cleaners, oxidizers or other cleaning products. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Wear rubber gloves and protective eyewear when handling. Wash hands after each use. Avoid breathing of vapors. Use in well-ventilated area only. Avoid contact with aluminum, brass, iron and strong alkaline cleaners or bleaches

#### SECTION 7-HEALTH HAZARDS AND FIRST AID

#### Effects of Overexposure:

**Skin:** Severe skin irritant. Prolonged or repeated contact will cause permanent chemical

Eyes: Severe eye irritant. Liquid and mists will burn or injure eyes, causing permanent corneal damage.

Inhalation: Strong irritant to mucous membranes of the nose, throat, and lungs. Vapors may cause choking, burning sensation of throat and lungs, leading to irreversible damage. May be fatal. Chronic exposure may damage teeth.

Ingestion: Irritating and corrosive to the mouth and throat on immediate contact. May be fatal. Cause severe ulceration of mucous membranes.

#### **First Aid Procedures:**

Skin: Immediately remove contaminated clothing. Flush exposed area with large quantities of water followed by washing with mild soap. Seek medical attention immediately.

Eyes: Immediately flush with large quantities of water for at least 15 minutes, holding eyelids open. Seek medical attention immediately.

Inhalation: Get to fresh air. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Drink large quantities of water. Seek medical attention immediately.

#### SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH approved acid-gas air purifying canister when used in confines or poorly ventilated areas

Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredient (Hydrochloric Acid) below acceptable limit.

Protective Gloves: Full arm length acid proof, rubber, or neoprene. Eye Protection: Chemical splash goggles or full-face safety shield.

Other Protective Equipment: Evewash station should be made available near site where used. Chemical resistant apron should be worn when danger of splash contact will occur.

#### SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Immediately evacuate all unessential personnel from area. Ventilate area well. Acquire special protection equipment as noted in Section 8. Absorb spill with inert material. Neutralize with soda ash or lime. Avoid discharge to sewer or open waterways.

Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. If disposed of in its purchased form, this product has the RCRA characteristic of corrosivity and would have an EPA Hazardous waste number of D002. Consult local authorities for disposal in public sewer. Do not disposal of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

#### SECTION 10-REGULATORY INFORMATION

### SARA Title III - Section 311/312 - Hazard Categories:

No - Fire Hazard

No - Sudden Release of Pressure Hazard

No - Reactivity Hazard

Yes - Immediate (acute) Health Hazard No - Delayed (chronic) Health Hazard

**Shipping Information:** 

FOR CONTAINERS > 1 Gallon: Compounds, cleaning liquid,

(hydrochloric acid), 8, NA-1760, PG II

FOR 1 GALLON CONTAINERS: Compounds, cleaning liquid,

(hydrochloric acid), 8, NA-1760, PG II FOR CONTAINERS < 1 GALLON: ORM-D **HMIS Hazardous Materials** Identification System

Health Flammability Reactivity **Personal Protection** 

N/A=Not Applicable

#### FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS# Chemical Name Percent by Weight Exempt None

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

Chemical Name Percent by Weight CAS#

None

#### SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product