MATERIAL	SAFE	ΓΥ D	ATA	SHE	ET			
OSHA - Meets 29 CFR 1910.1200 Standards HMIS HAZARD RATINGS								
	HEALTH FLAMMABILIT PHYSICAL HA		0	* = Chronic Hea 0 = INSIGNIFICA 1 = SLIGHT		2 = MODEF 3 = HIGH 4 = EXTRE		
agens				ION INFORM				
BRAND, INC.	PROPER SHIP HAZARD CLAS IDENTIFICATIO	SS / PKG GRP: ON NUMBER:		iquid, acidic, inor REF: LABE	49 CFR	173.154, .203		
SECTION 1 - PRODUCT / COMPAN	Y IDENTIFI	CATION						
IDENTITY (AS USED ON LABEL AND LIST) <i>Z - 920</i>						Page 1 of 2		
MANUFACTURER'S NAME Zagers Brand, Inc		ChemTel	Inc. 1- (80	HONE NUMBE 0) 255-3924	Intl. + 01 (81	3) 248-0585	5	
ADDRESS (NUMBER, STREET, P.O. BOX) 4320 Gandy Blvd		TELEPHO (800) 999		R FOR INFOR				
(CITY, STATE AND ZIP CODE) Tampa, FL 33611		DATE PRE SUPERSE		November 20 New	0, 2007			
SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION								
HAZARDOUS COMPONENTS	1	%	OSHA		CGIH TWA	SARA	RQ	
(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	(OPTIONAL)	PPM	MG/M3 PP	M MG/M3		LBS	
Phosphoric acid (a)	7664-38-2	5 - 10		1		1	5000	
Hydroxyacetic acid	79-14-1	1 - 5	not est	tablished				
(a) The Comprehensive Environmental Response, Compensa environment of the Reportable Quantity (RQ for this mixture > SECTION 3 - HEALTH HAZARD DA	24,000 lbs) or gre				or releases or	spills to the		
ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE		EMERGENC	AND FIRST	AID PROCEDURE	S			
INHALATION: Corrosive and irritating to upper respiratory tract.		Remove affected person to fresh air; if breathing has not returned to normal within a few minutes after exposure, get medical attention.						
SKIN: Corrosive and irritating; chemical burns may result from contact.		Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.						
EYES: Corrosive; Causes immediately severe irritation of the eye and eyelids. If not quickly removed by thorough irrigation with water, there may be prolonged or permanent visual impairment or total loss of sight		Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention immediately.						
INGESTION: Corrosive to the mucous lining of the mouth, throat, esophagus and stomach		Drink two glasses of water followed by milk, milk of magnesia or other non- alcoholic liquids; DO NOT induce vomiting; seek medical attention immediately.						
CARCINOGENICITY California Prop 65, Safe Drinking Water and Toxic Enforceme reproductive toxicity.		ere are no repo	table chemic	-	n to the state			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY E prolonged exposure.	XPOSURE: Preex	isting skin, eye	, or respirator	y disorders may	become aggra	avated throug	h	

IDENTITY (AS USED ON LABEL AND LIST)		
DENTITY (NO OBED ON EXBEETIND EIGT)		Page 2 of 2
Z - 920	Date: November 20, 2007	
SECTION 4 - FIRE FIGHTING MEASURI	ES	
FLASH POINT (METHOD USED)	NFPA RATING	FLAMMABLE LIMITS
Non-flammable	None	LEL: Not applicable UEL: Not applicable
EXTINGUISHING MEDIA		
Carbon dioxide, water, water fog, dry chemical, chemical foam SPECIAL FIRE FIGHTING PROCEDURES		
Keep containers cool with water spray to prevent container rupture of	due to steam buildup; flo	or will become slippery if material is released. CAUTION -
material is corrosive.	• •	
UNUSUAL FIRE AND EXPLOSION HAZARDS		
Contact with B:C extinguisher powder may produce large amounts of	of carbon dioxide.	
SECTION 5 - ACCIDENTAL RELEASE M		
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILI		
confine spill, soak up with approved absorbent, shovel product into ap National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR		
National Response Center (800) 424 - 8802, Teler to CERCLA 40 CFR		aons concerning reporting requirements.
	. <u></u>	
SECTION 6 - HANDLING AND STORAG		
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Kee		
temperatures. Separate from oxidizing materials, metallic powders an	nd other easily oxidized o	organic materials and reducing agents. CAUTION - material is
corrosive. Keep this and other chemicals out of reach of children.		
SECTION 7 - EXPOSURE CONTROLS / I	PERSONAL PI	ROTECTION
RESPIRATORY PROTECTION (SPECIFY TYPE): None required whi		
exceeds limits, NIOSH approved respirator must be worn. Refer to 29) CFR 1910.134 or Euro	pean Standard EN 149 for complete regulations.
VENTILATION LOCAL EXHAUST: Require		.: To maintain minimum TWA and STEL levels.
MECHANICAL (GENERAL): Yes		R: Engineering and work controls as required.
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apro		ECTION: Protective eyeglasses or chemical safety goggles.
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Mi		
SECTION 8 - PHYSICAL / CHEMICAL PRO		
BOILING POINT	· · · · · · · · · · · · · · · · · · ·	GRAVITY (WATER = 1)
212° F	1.060	
VAPOR PRESSURE (MM Hg)	pН	
	рН 1.0 - 2.0)
VAPOR PRESSURE (MM Hg)	1.0 - 2.0) ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1	1.0 - 2.0 EVAPOR/ < 1	ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER	1.0 - 2.0 EVAPOR/ < 1 % VOLAT	
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete	1.0 - 2.0 EVAPOR/ < 1	ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR	1.0 - 2.0 EVAPOR/ < 1 % VOLAT	ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor	1.0 - 2.0 EVAPOR < 1 % VOLAT 82%	ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIV	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE:	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE:	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT)
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong	1.0 - 2.0 EVAPOR, <1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition	1.0 - 2.0 EVAPOR, < 1 % VOLAT 82%	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	I.0 - 2.0 EVAPOR, < 1 % VOLAT 82% //// CONDITIO ng acids, strong alkalies n will not occur if handle CONDITIO None	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon,
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR:	I.0 - 2.0 EVAPOR, < 1 % VOLAT 82% //// CONDITIO ng acids, strong alkalies n will not occur if handle CONDITIO None	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon,
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVA STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	I.0 - 2.0 EVAPOR, <1 % VOLAT 82% //// CONDITIO ng acids, strong alkalies n will not occur if handle CONDITIO None	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID:
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X SECTION 10 - DISPOSAL CONSIDERAT WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S 299" for complete waste disposal regulations for corrosive materials.	1.0 - 2.0 EVAPOR, <1 % VOLAT 82% //// CONDITIO ng acids, strong alkalies n will not occur if handle CONDITIO None //ONS State, and Federal Regu	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 -
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X SECTION 10 - DISPOSAL CONSIDERAT WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S	1.0 - 2.0 EVAPOR, <1 % VOLAT 82% //// CONDITIO ng acids, strong alkalies n will not occur if handle CONDITIO None //ONS State, and Federal Regu	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 -
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIV STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X SECTION 10 - DISPOSAL CONSIDERAT WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S 299" for complete waste disposal regulations for corrosive materials. any chemicals.	1.0 - 2.0 EVAPOR, <1	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 - e, or Federal Environmental Protection Agency before disposing c
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X SECTION 10 - DISPOSAL CONSIDERAT WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S 299" for complete waste disposal regulations for corrosive materials. any chemicals.	1.0 - 2.0 EVAPOR, <1	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 - a, or Federal Environmental Protection Agency before disposing c Data and calculations: are based on information furnished by th
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor SECTION 9 - STABILITY AND REACTIVE STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X SECTION 10 - DISPOSAL CONSIDERAT WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S 299" for complete waste disposal regulations for corrosive materials. any chemicals.	1.0 - 2.0 EVAPOR, <1	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 - e, or Federal Environmental Protection Agency before disposing of Data and calculations: are based on information: furnished by the
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C VAPOR DENSITY (AIR = 1) > 1 SOLUBILITY IN WATER Complete APPEARANCE AND ODOR Green liquid, "Downy" odor <i>SECTION 9 - STABILITY AND REACTIV</i> STABILITY UNSTABLE: STABLE: X INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, stron HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition hydrocarbons, fumes, and smoke may be produced. HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X <i>SECTION 10 - DISPOSAL CONSIDERAT</i> WASTE DISPOSAL METHOD: Dispose of in accordance with Local, S 299" for complete waste disposal regulations for corrosive materials. any chemicals.	1.0 - 2.0 EVAPOR, <1	ATION RATE (WATER = 1) ILE (BY WEIGHT) NS TO AVOID: Extreme temperatures d and stored properly. In case of a fire, oxides of carbon, NS TO AVOID: lations. Refer to "40 CFR Protection of Environment Parts 260 - b, or Federal Environmental Protection Agency before disposing of Data and calculations: are based on information: furnished by the advised to confirm in advance of need that information is current to vendee or third persons proximately caused by abnormal up